

intimus VZ 17.00 | VZ 18.00

High performance modular shredding system for customised solutions

This concept assures fulfilment of your requirements and provides you with performance reserves at favorable attractive investment costs. Competent contact persons are available to provide you with accurate advice and assistance for all of your questions and concerns. Many years of experience enable us to offer quick, efficient solutions which fulfil your individual requirements.



Each project is implemented in a clear-cut, logical fashion, allowing you to follow the development of your shredder in detail, and issue manufacturing approval with confidence.

- Shreds paper and cardboard
- Two shredding steps: From primary shredder – 30 mm strip cut – particles fall onto a conveyor belt and are transported directly to the cutting shafts of the security shredder
- Automatic feed of material to pre-shredder via large feed conveyor and hopper
- PLC-control with touchscreen
- Precision cutting cylinders made from special hardened steel allow for high throughput volumes with minimal wear and low power consumption
- Specially suited storage and compacting equipment is recommended for further processing of shredded particles. Simple storage solutions (containers), as well as specially configured compacting equipment for volume reduction can be supplied upon request.



Model	Shred size		Security level DIN 66399						Actual throughput**	Motor power	Fusing	Shreds additionally:				
	mm		P	F	O	T	H	E				kg/h	kW	A		
VZ 17.00	6 x 15-50	70+	3	-	3	3*	-	2	600	15.8	63	✓	✓	✓	✓	✓
VZ 18.00	11.8 x 15-55	100+	2	-	2	2*	-	2	850	17.5	80	✓	✓	✓	✓	-

* only floppy disks / ID cards
 ** = certain small format items – such as SSD – may go through the cutting mechanism **undestroyed**

Dimensions – with standard feed conveyor
In-line set-up cm / W = 520 D = 100 H = 270
Angular set-up 90° cm / W = 420 D = 220 H = 270

Optional Equipment
 Extensive assortment of accessories available on request